



SPECIFICATION FOR LINED PIPES

NB	ØA (± 1)	B	ØC	PCD	ØE	No. of Holes	Hole. Dia
15	10.8	15.8	34.9	60.3	88.9	4	15.9
20	16.0	21.0	42.7	69.8	98.4	4	15.9
25	21.6	26.6	50.8	79.4	108.0	4	15.9
32	28.1	35.1	63.5	88.9	117.5	4	15.9
40	33.9	40.9	73.0	98.4	127.0	4	15.9
50	45.5	52.5	92.1	120.7	152.4	4	19.0
65	55.7	62.7	104.8	139.7	177.8	4	19.0
80	70.9	77.9	127.0	152.4	190.5	4	19.0
100	95.3	102.3	157.2	190.5	228.6	8	19.0
125	119.2	128.2	185.7	215.9	254.0	8	22.2
150	145.1	154.1	215.9	241.3	279.4	8	22.2
200	196.1	205.1	269.9	298.5	342.9	8	22.2
250	246.4	257.4	323.9	362.0	406.4	12	25.4
300	296.0	307.0	381.0	431.8	482.6	12	25.4

1. All dimensions are in millimeters.
2. Fixed/loose/split flanges on one /both sides can be supplied on request.
3. Other specifications/dimensions/vacuum service available on request.
4. Lengths: 3 meter lengths
 longer Lengths available on request
 Tolerance upto 1 meter length will be + 0.0mm/ -3.5mm and
 beyond 1 meter will be +0.0mm/ -5.0mm.